


















Part Number	Illustration	Description
rpr-IoT-AT01		Indoor Ambient Temperature Node
rpr-IoT-T01-1		rpr-IoT-T01 Temperature Node with probe
rpr-IoT-T02-1-1		rpr-IoT-T02 Dual Temperature Node with 2 probes
rpr-IoT-TP01		Temperature Probe s/s 1m
WS-EML-S-860-050		EML SS5/12 Non-Aspirated Sensor Screen & bracket
rpr-IoT-R01		rpr-IoT-R01 Rain node with 2m cable (without rain gauge)
WS-EML-KALYXRG-P-780-701		Kalyx-RG Rain gauge White 0.2mm (without baseplate and pole mounting arm)
WS-EML-KALYXBPMA-P-780-781		Baseplate+Mast Mounting Arm for Kalyx Rain gauge
rpr-IoT-SR01		rpr-IoT-SR01 Solar Radiation Node (without sensor)

Part Number	Illustration	Description
rpr-IoT-SR02		Solar & Temperature Node (without sensors)
rpr-IoT-ML01		Si-Pyranometer (Class C) with 5m cable & connector
rpr-IoT-SW01		Switch node
rpr-IoT-GW-868		LoRaWAN indoor gateway EU868
rpr-IoT-BAT-A		Lithium Thionyl Chloride (LiSOCl ₂) A size battery
rpr-IoT-C5B		Connector, 5-way, blue, for Pyranometer
rpr-IoT-BCAP		Connector blanking cap
rpr-IoT-dashboard		rpr-IoT Dashboard - user configurable to display data and status information from sensor nodes
rpr-IoT-OEM		Customised IoT solutions. Please contact sales@r-p-r.co.uk